

ARMOR COAT

**AN ALL NEW REVOLUTIONARY COATING THAT IS RESISTANT TO ABRASION, IMPACT, OXIDATION, CORROSION.
100% CHEMICALLY RESISTANT**

DIRECTIONS:

Clean surface thoroughly, using heavy duty cleaners and degreasers. All oil, grease, dirt, paint etc., must be completely removed prior to application of **ARMOR COAT**. For best results, acid etch surface following cleaning, thoroughly rinse and allow surface to dry completely.

Mix well before applying. May be applied by brush, roller or spray.

Two or more coats may be required depending upon the porosity of the surface and appearance level desired. Apply thin coats. After first coat is applied, allow it to dry. Apply second coat before 24 hours have expired. If second coat is applied after 24 hours, surface should be lightly sanded to remove gloss. This will assure bonding of second coat.

Allow 24 hours for surface to dry, before re-opening to traffic.

- Use with adequate ventilation.
- Keep out of reach of children.
- For commercial, industrial and institutional use only.

Danger: Harmful if swallowed. If swallowed, do not induce vomiting. Call physician immediately.

Caution: Combustible: Keep from heat or open flame. Avoid prolonged or repeated breathing of vapors and prolonged or repeated contact with skin. Use with adequate ventilation. Do not take internally. Before smoking, eating or after using, cleanse hands thoroughly. Keep container closed.



E.L.S. Products Corp

1-800-528-4861