

PERMANENT PATCH

THREE PART EPOXY SYSTEM

Permanent Patch is a unique and complete epoxy mortar system. Usage is simple, even under the most extreme conditions. When mixed, Permanent Patch provides a high strength patching mortar, which can be feather edged.

Permanent Patch is unique in its ability to bond to damp surfaces at cold temperatures, while being 100% chemical resistant, making it the right choice for outdoor as well as indoor applications. Early high tensile strength eliminates down time making Permanent Patch suitable for heavy industrial and plant use where curing time is a factor.

Easy to Apply. No special tools required.

Directions:

- Clean surface of loose aggregate, dust, oil and grease. For best results, wash surface with muriatic acid and flush with clean water. Allow to dry. Pour all container B into container A, mix thoroughly. Let stand 10-15 minutes for activation.
- Use paint type mechanical mixer when possible.
- Add aggregate to mixture and mix thoroughly.
- Apply on surface, using a wet trowel for a smooth finish.
- Pot life approximately 60 minutes.
- Permanent Patch is designed to fill-in and re-surface cracks, holes in: concrete - brick - metal - wood and any other surface such as curbing and steps.
- PermanentPatch can also be used for anchoring machinery, equipment and all types of structural metal.

CAUTION: Harmful if swallowed



E.L.S. Products Corp.

1.800.528.4861